


Model: EURO GNE 3

Technical features

Reference	Model type	Energy efficiency class	Energy efficiency index (%)	Energy consumption over 24 hours (E24h)	Annual energy consumption (kWh)	Net volume (l)	Climate class	No.doors	Connection power (W)	W x D x H dimensions (mm)
19023482	COUNTER CABINET	D	52,9	3	1230	210	4	3	414	1792 x 700 x 850



Packaging dimensions:

Depth: 825,000 MM

Width: 1.910,000 MM

Height: 1.085,000 MM

Gross weight: 150,000 KG

General characteristics

The top is fitted with a 340 x 340 x 200 mm sink.
 Compact design fully injected with stainless steel exterior panels.
 Internal body made of stainless steel.
 Doors with handles made of stainless steel.
 Doors equipped with self-closing hinge system and opening stopper.
 Doors made in stainless steel, strong with high thermal insulation. Incorporate easily replaceable sealing strips.
 Internal shelves made with plastic-coated wires, easily removable for cleaning.
 Height-adjustable fastening brackets for shelves.
 Height-adjustable stainless steel feet.
 Drain inside the chamber.
 Control panel and engine ventilation with pivoting front opening.
 Sealed condensing unit with ventilated condenser.
 R-134 A CFC – Free Ecologic Refrigerant.
 Forced draft evaporator with anticorrosion coating.
 Automatic defrost evaporation.
 CFC-free, injection-moulded polyurethane insulation with a density of 40 Kg/m³.
 Start-stop light switch.
 High-class controller with a digital temperature display conformant to the HACCP system.
 Temperature range: from -2 °C to +8 °C.
 Standard: 1 GN 1/1 rack and two sets of guides per door.
 Supply voltage: 230 V 1+N – 50 Hz.
 Available either with solid doors or with glazed doors.
 Suitable to be placed in one line with EDESA neutral furniture.



Spare parts

Reference	SAP reference	Description	Recommended	Replaced	Price
-----------	------------------	-------------	-------------	----------	-------